



HPE ProLiant DL160 Gen9 Server



Specifications

Processor family

Intel® Xeon® E5-2600 v3 product family; Intel® Xeon® E5-2600 v4 product family





Number of processors

1 or 2

Processor core available

18 or 16 or 14 or 12 or 10 or 8 or 6 or 4

Form factor (fully configured)

1U

Power supply type

(2) Entry-Level

Expansion slots

(3) Maximum - For detail descriptions reference the QuickSpecs

Memory, maximum

1TB

Memory slots

16 DIMM slots

Memory type





DDR4 SmartMemory

Drive description

(8) SFF SAS/SATA/SSD; (4) LFF SAS/SATA/SSD; Hot plug and/or Non-hot plug, depending on model

Network controller

1Gb 361i Ethernet Adapter 2 Ports per controller and/or; Optional FlexibleLOM on riser; Depending on model

Storage controller

(1) Dynamic Smart Array B140i or; (1) H240 Host Bus Adapter; (1) Smart Array P440; Depending on model

Infrastructure management

iLO Management (standard), Intelligent Provisioning (standard), iLO Essentials(optional), iLO Scale-Out(optional) iLO Advanced (optional)

Warranty

3/1/1 Server Warranty includes three years of parts, one year of labor, one year of onsite support coverage. Additional information regarding worldwide limited warranty and technical support is available at: www.hpe.com/services/support. Additional Hewlett Packard Enterprise support and service coverage for your product can be purchased locally. For information on availability of service upgrades and the cost for these service upgrades, refer to www.hpe.com/services/support.

Memory protection features

Advanced ECC; Memory Online Spare Mode; Memory Mirroring Mode





Processor cache

10MB LLC; 15MB LLC; 20MB LLC; 25MB LLC; 30MB LLC; 35MB LLC; 40MB LLC; 45MB LLC

Processor speed

3.0GHz

Form factor chassis

Rack

System fan features

Hot plug redundant optional

